

TYPICAL PROPERTY

GRADE 8725 DA(MATTE)

*Raw Material BOPP MATTE FILM

Thickness 13micron±4%

DESCRIPTION Polypropylene film with copolymer adhesive. This film offers economy easy separation and acid-resistant properties.

APPLICATION For one sided finishing applications on soft cover books, brochures, book jacket, box etc.

VALIDITY OF THERMAL LAMINATING FILM

Use film within 10 months after produced.

ENVIRONMENTAL CONDITION WHILE USING

Temperature : 24°C ± 20%

Relative Humidity: 60% ± 16.5%

STORAGE CONDITION

Temperature : 24°C ± 20%

Relative Humidity: 60% ± 16.5%

CONSTRUCTION

Grade	Surface	Thickness (Micron)	Width (mm)	Length (M)	Core Size (inside)	Adhesive
8725 DA	MATTE	25±6.6%	STD	STD	3	Inside

TYPICAL PROPERTY

Properties		8725 DA	Unit	Test Method
Tensile Strength	MD	6.8 ± 20%	KG/SQ.MM	ASTM D882
	TD	11.0 ± 20%	KG/SQ.MM	
Elongation	MD	190 ± 20%	%	ASTM D882
	TD	60 ± 20%	%	
Haze		94.0 ± 1%	%	ASTM D1003
Gloss		6.6 ± 10%		ASTM D2457
Heat Shrinkage	MD	3.6 ± 0.5	%	ASTM D1204
	TD	2.0 ± 0.3	%	
Corona	EVA LAYER	44 and over	dyne	ASTM D2578
	OPP SIDE	36 - 42	dyne	

Rev. NO: 01

Cosmo Films Korea Co. Ltd.,